

NEW

Digital Anemometer

HT625A/B

Specifications	Range	Resolution	Accuracy	
			HT625A	HT625B
Range of Air speed	0.40~30.00m/s	0.01	±(2.0%+ 0.5m/s)	±(2.0%+ 0.5m/s)
	1.40~108.0km/h	0.01~0.1	±(2.0%+ 1.8km/h)	±(2.0%+ 1.8km/h)
	1.30 ~ 98.50ft/s	0.01	±(2.0%+ 1.6ft/s)	±(2.0%+ 1.6ft/s)
	0.80 ~ 58.30Knots	0.01	±(2.0%+ 1.0knots)	±(2.0%+ 1.0knots)
	0.90 ~ 67.10mile/h	0.01	±(2.0%+ 1.1mile/h)	±(2.0%+ 1.1mile/h)
	78.00~ 5900ft/m	0.01~1	±(2.0%+ 10ft/m)	±(2.0%+ 10ft/m)
Range of Air volume	0- 9999 CFM(CMM、CMS)	0.01~0.1		
Air temperature	-20~60°C(-14~140°F)	0.1		±1.5°C
Dew point temperature of air	-20~60°C (-4~140°F)	0.1		±1.5°C
Wet bulb temperature	-50~60°C (-58~140°F)	0.1		±1.5°C
Air humidity	0~99%	0.1		±4.0%
USB				✓
Display			9999 counters with bargraph	9999 counters
Features				
Air duct area setting	✓			
Data hold	✓			
MAX/MIN/AVG hold	✓			
Auto Power Off	✓			
Low battery indication	✓			
General				
Power	3x1.5V AAA batteries			
Weight	Approx.180g			
Size	197mmX60mmX33mm			

